

Moulded tiles and accessories for the twin trough gutter tile D 13

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.


	Whole tile Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Weight: ~ 3.5 kg Requirement: ~ 12.8 pcs/m ²		Ceramic vent pipe tile with weather cap ø 125 and hose with adapter Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Weight: ~ 5.0 kg Requirement: individual
	Half tile Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 14.6 cm Covering width: ~ 10.7 cm Weight: ~ 2.1 kg Requirement: individual		PVC thermal exhaust gas through tile ø 100/125 (can be used up a max of 40° RP*) Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm
	Double flap Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 23.8 cm Covering width: ~ 23.8 cm Weight: ~ 3.8 kg Requirement: ~ 2.8 pcs/m		Walking grid tile PVC x 2 + walking grid Width: ~ 34.0 cm Length: 40.0; 80.0; 150.0 cm
	Verge tile with outer web on left Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 23.8 cm Covering width: ~ 21.7 cm Weight: ~ 5.1 kg Requirement: ~ 2.8 pcs/m		SnapStep universal alu step coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°
	Verge tile with outer web on right Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 24.2 cm Covering width: ~ 18.0 cm Weight: ~ 5.4 kg Requirement: ~ 2.8 pcs/m		SnapStep 40 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°
	Ridge/crest tile ~ 2.7 pieces/m Length: ~ 43.5 cm Covering length: ~ 37.0 cm Width: ~ 24.5 cm Covering width: ~ 21.2 cm Weight: ~ 3.4 kg Requirement: ~ 2.7 pcs/m		SnapStep 80 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°
	Standard start ridge with end web with extended web for verge tile with outer web Length: ~ 43.5 cm Covering length: ~ 30.5 cm Width: ~ 24.5 cm Covering width: ~ 21.2 cm		Safety step tile, PVC Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Weight: ~ 3.6 kg Requirement: individual
	End ridge with end web with extended web for verge tile with outer web Length: ~ 43.5 cm Covering length: ~ 37.0 cm Width: ~ 24.5 cm Covering width: ~ 21.2 cm		Snow stop tile with round wood holder PVC Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Weight: ~ 1.2 kg Requirement: individual
	Crest initial tile Length: ~ 43.4 cm Covering length: ~ 29.5 cm Width: ~ 23.1 cm Covering width: ~ 21.2 cm Weight: ~ 3.2 kg Requirement: individual		Snow stop tile with snow rib support PVC Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Weight: ~ 1.2 kg Requirement: individual
	Hip cap start and end Requirement: individual		PVC solar through tile Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Weight: ~ 0.7 kg ø: 30/50/70 mm
	Hip cap start and end with four outlets Requirement: individual		PVC solar carrier tile Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Weight: ~ 2.4 kg Requirement: individual
	Shed roof tile Length: individual Covering length: individual Width: ~ 25.5 cm Covering width: ~ 21.5 cm		Light tile „Acrylic glass“ Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Requirement: individual
	Half shed roof tile Length: individual Covering length: individual Width: ~ 14.6 cm Covering width: ~ 10.7 cm		Steel skylight, coated, 6-tiles, acrylic glazed Length: ~ 78.0 cm Hatch: 45.0 x 55.0 cm Width: ~ 76.0 cm Weight: ~ 8.6 kg
	Shed roof-Double flap Length: individual Covering length: individual Width: ~ 23.8 cm Covering width: ~ 23.8 cm		Multitherm skylight Length: ~ 85.0 cm Opening: upwards + to the side Width: ~ 78.0 cm Hatch: 44.0 x 54.0 cm Weight: ~ 15.0 kg Double glazing: ESG Kv 1.4
	Shed roof-verge tile with outer web on left Length: individual Covering length: individual Width: ~ 23.8 cm Covering width: ~ 21.7 cm		Living room skylight wra Length: ~ 98.0 cm Opening: to the side Width: ~ 54.0 cm Hatch: 46.0 x 90.0 cm Double glazing: ESG Kv 1.1
	Shed roof-verge tile with outer web on right Length: individual Covering length: individual Width: ~ 24.2 cm Covering width: ~ 18.0 cm		Eaves fresh air element ~ 1.1 pcs/m
	Clay dormer ventilator (ventilation cross-section ~ 15 cm²) Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Weight: ~ 3.7 kg Requirement: individual		Ridge/crest lath holder
	Ceramic aerial tile Length: ~ 43.9 cm Covering length: ~ 36.5 cm ± 3 mm Width: ~ 25.5 cm Covering width: ~ 21.5 cm Weight: ~ 4.3 kg Requirement: individual		

Moulded tiles and accessories for the twin trough gutter tile D 13

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

Ridge or crest clip no. 470/41



Storm clip no. 435/001 for laths 30 x 50 V2A (1)

Storm clip no. 435/002 for laths 40 x 60 V2A (1)

Storm clip no. 409/002 V2A (2)

Copper roll/Alu roll 2000

Length: ~ 5 m Width: ~ 29 cm, 33 cm, 36 cm

Ventilation cross-section: permanent acc. to DIN 4108, Part 3

Natural copper, anthracite, red

