

Moulded tiles and accessories for the NIBRA® flat roof tile F 10 Ü

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	Whole tile Length: ~ 48.2 cm Width: ~ 29.2 cm Weight: ~ 4.5 kg	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: ~ 10.0 pcs/m ²		Start ridge extra closed at bottom for verge tile with offset web Length: ~ 44.0 cm Width: ~ 27.0 cm	Covering length: ~ 38.5 cm Covering width: ~ 21.2 cm
	Large-area tile with nail hole* Length: ~ 48.2 cm Width: ~ 29.2 cm Weight: ~ 4.5 kg	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: ~ 10.0 pcs/m ²		End ridge extra closed at bottom for verge tile with offset web Length: ~ 38.3 cm Width: ~ 27.0 cm	Covering length: ~ 36.3 cm Covering width: ~ 21.2 cm
	Double flap Length: ~ 48.2 cm Width: ~ 32.4 cm Weight: ~ 5.2 kg	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 32.4 cm Requirement: ~ 2.5 pcs/m		Shed roof tile Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 24.0 cm
	Half tile Length: ~ 48.2 cm Width: ~ 17.0 cm Weight: ~ 2.6 kg	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 11.9 cm		Shed roof-Double flap Length: individual Width: ~ 32.4 cm	Covering length: individual Covering width: ~ 32.4 cm
	Left verge tile Length: ~ 48.2 cm Width: ~ 32.4 cm Weight: ~ 6.3 kg	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: ~ 2.5 pcs/m		Shed roof-left verge tile Length: individual Width: ~ 32.4 cm	Covering length: individual Covering width: ~ 24.0 cm
	Right verge tile Length: ~ 48.2 cm Width: ~ 29.2 cm Weight: ~ 5.9 kg	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 15.2 cm Requirement: ~ 2.5 pcs/m		Shed roof-Right verge tile Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 15.2 cm
	Standard ridge tile ~ 2.6 pcs/m Length: ~ 43.7 cm Width: ~ 25.4 cm Weight: ~ 3.6 kg	Covering length: ~ 38.2 cm Covering width: ~ 19.6 cm Requirement: ~ 2.6 pcs/m		Eaves tile Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm
	Standard start ridge, bottom closed for verge tile with offset ridge Length: ~ 43.7 cm Width: ~ 25.4 cm	Covering length: ~ 38.2 cm Covering width: ~ 19.6 cm		Eaves Double flap Length: ~ 48.2 cm Width: ~ 32.4 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 32.4 cm
	Standard ridge end, bottom closed for verge tile with offset ridge Length: ~ 38.0 cm Width: ~ 25.4 cm	Covering length: ~ 36.0 cm Covering width: ~ 19.6 cm		Eaves left verge tile Length: ~ 48.2 cm Width: ~ 32.4 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm
	Standard crest start Length: ~ 49.0 cm Width: ~ 25.4 cm Weight: ~ 3.5 kg	Covering length: ~ 43.9 cm Covering width: ~ 19.6 cm Requirement: individual		Eaves right verge tile Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 15.2 cm
	Universal hip cap Weight: ~ 4.5 kg	Requirement: individual		Mansard tile Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 24.0 cm
	Universal hip cap with four outlets Weight: ~ 6.3 kg	Requirement: individual		Mansard-Double flap Length: individual Width: ~ 32.4 cm	Covering length: individual Covering width: ~ 32.4 cm
	Clay dormer ventilator (ventilation cross-section ~ 17 cm²) Length: ~ 48.2 cm Width: ~ 29.2 cm Weight: ~ 4.2 kg	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: individual		Mansard-left verge tile Length: individual Width: ~ 32.4 cm	Covering length: individual Covering width: ~ 24.0 cm
	Ridge connecting tile Length: ~ 48.2 cm Width: ~ 29.2 cm Weight: ~ 4.2 kg	Covering length: ~ 40.0 cm ± 10 mm Covering width: ~ 24.0 cm		Mansard-right verge tile Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 15.2 cm
	Ridge connecting Double flap Length: ~ 48.2 cm Width: ~ 32.4 cm Weight: ~ 5.5 kg	Covering length: ~ 40.0 cm ± 10 mm Covering width: ~ 32.4 cm		Pent roof tile Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 24.0 cm
	Ridge connection-verge tile left Length: ~ 48.2 cm Width: ~ 32.4 cm Weight: ~ 7.4 kg	Covering length: ~ 40.0 cm ± 10 mm Covering width: ~ 24.0 cm		Pent roof-Double flap Length: individual Width: ~ 32.4 cm	Covering length: individual Covering width: ~ 32.4 cm
	Ridge connection-verge tile right Length: ~ 48.2 cm Width: ~ 29.2 cm Weight: ~ 6.0 kg	Covering length: ~ 40.0 cm ± 10 mm Covering width: ~ 15.2 cm		Pent roof-left verge tile Length: individual Width: ~ 32.4 cm	Covering length: individual Covering width: ~ 24.0 cm
	Ridge tile extra ~ 2.6 pcs/m (matches ridge connecting tile) Length: ~ 44.0 cm Width: ~ 27.0 cm	Covering length: ~ 38.5 cm Covering width: ~ 21.2 cm		Pent roof-right verge tile Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 15.2 cm

* Delivery period on request

Moulded tiles and accessories for the NIBRA® flat roof tile F 10 Ü

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	Wall connection tile Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 24.0 cm		Alu base tile with single step Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: individual
	Wall connection Double flap Length: individual Width: ~ 32.4 cm	Covering length: individual Covering width: ~ 32.4 cm		Alu base pantile with twin tube holder Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: individual
	Wall connection left verge tile Length: individual Width: ~ 32.4 cm	Covering length: individual Covering width: ~ 24.0 cm		Alu tile with round wood holder Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: individual
	Wall connection right verge tile Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 15.2 cm		Alu tile with snow rib support Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: individual
	Ceramic vent pipe tile with weather cap ø 150 and matching hose with adapter Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: individual		Light tile „Acrylic glass“ Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm
	Ceramic aerial tile Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: individual		Steel skylight, coated, 4-tiles, acrylic glazed Hatch: 45.0 x 55.0 cm	
	Ceramic thermal exhaust gas through pantile with universal collar (ø: max. 127 mm) (can be used up a max of 42° RP*) Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm		Multitherm skylight Length: ~ 85.0 cm Width: ~ 78.0 cm Weight: ~ 15.0 kg	Opening: upwards + to the side Hatch: 44.0 x 54.0 cm Double glazing: ESG Kv 1.4
	Ceramic solar through tile up to ø 70 mm Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm ø: ≤ 70 mm		Living room skylight wra Length: ~ 98.0 cm Width: ~ 54.0 cm	Opening: to the side Hatch: 46.0 x 90.0 cm Double glazing: ESG Kv 1.1
	PVC solar carrier tile Length: ~ 48.2 cm Width: ~ 29.2 cm	Covering length: ~ 41.3 cm ± 12 mm Covering width: ~ 24.0 cm Requirement: individual		Eaves fresh air element ~ 1.1 pcs/m	
	2 Alu-walking grid tile, coated Width: ~ 34.0 cm Length: 40.0; 80.0; 150.0 cm			Ridge/crest lath holder	
	SnapStep universal alu step coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°			Ridge or crest clip no. 470/41	
	SnapStep 40 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°			Copper roll/Alu roll 2000 Length: ~ 5 m Width: ~ 29 cm, 33 cm, 36 cm	Ventilation cross-section: permanent acc. to DIN 4108, Part 3 Natural copper, anthracite, red
	SnapStep 80 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°			Multi storm claw	

* Over 42° RP = special design of PVC on request