

Moulded tiles and accessories for the flat roof tile F 12 Ü

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	Whole tile Length: ~ 45.7 cm Width: ~ 28.6 cm Weight: ~ 3.8 kg	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm Requirement: ~ 11.7 - 13.0 pcs/m ²		Mansard tile Length: individual Width: ~ 28.6 cm	Covering length: individual Covering width: ~ 23.6 cm
	Verge tile with outer web on left Length: ~ 45.7 cm Width: ~ 24.9 cm Weight: ~ 5.2 kg	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 22.0 cm Requirement: ~ 2.8 pcs/m		Mansard-verge tile with outer web on left Length: individual Width: ~ 24.9 cm	Covering length: individual Covering width: ~ 22.0 cm
	Verge tile with outer web on right Length: ~ 45.7 cm Width: ~ 24.1 cm Weight: ~ 5.0 kg	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 16.0 cm Requirement: ~ 2.8 pcs/m		Mansard-verge tile with outer web on right Length: individual Width: ~ 24.1 cm	Covering length: individual Covering width: ~ 16.0 cm
	Left verge tile Length: ~ 45.7 cm Width: ~ 28.9 cm Weight: ~ 4.1 kg	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 21.9 cm Requirement: ~ 2.8 pcs/m		Pent roof tile Length: individual Width: ~ 28.6 cm	Covering length: individual Covering width: ~ 23.6 cm
	Right verge tile Length: ~ 45.7 cm Width: ~ 28.9 cm Weight: ~ 4.0 kg	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 16.8 cm Requirement: ~ 2.8 pcs/m		Pent roof-verge tile with outer web on left Length: individual Width: ~ 24.9 cm	Covering length: individual Covering width: ~ 22.0 cm
	Ridge/crest tile ~ 2.7 pieces/m Length: ~ 43.5 cm Width: ~ 24.5 cm Weight: ~ 3.4 kg	Covering length: ~ 37.0 cm Covering width: ~ 21.2 cm Requirement: ~ 2.7 pcs/m		Pent roof-verge tile with outer web on right Length: individual Width: ~ 24.1 cm	Covering length: individual Covering width: ~ 16.0 cm
	Start ridge with offset end web for verge tile with offset ridge Length: ~ 43.5 cm Width: ~ 24.5 cm	Covering length: ~ 30.5 cm Covering width: ~ 21.2 cm		Ceramic vent pipe tile with weather cap ø 125 and hose with adapter Length: ~ 45.7 cm Width: ~ 28.6 cm Weight: ~ 7.8 kg	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm Requirement: individual
	Ridge end with offset end web for verge tile with offset ridge Length: ~ 43.5 cm Width: ~ 24.5 cm	Covering length: ~ 37.0 cm Covering width: ~ 21.2 cm		Ceramic aerial tile Length: ~ 45.7 cm Width: ~ 28.6 cm	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm Requirement: individual
	Crest initial tile Length: ~ 43.4 cm Width: ~ 23.1 cm Weight: ~ 3.2 kg	Covering length: ~ 29.5 cm Covering width: ~ 21.2 cm Requirement: individual		Ceramic thermal exhaust gas through pantile with universal collar (ø: max. 127 mm) (can be used up a max of 42° RP*) Length: ~ 45.7 cm Width: ~ 28.6 cm	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm Requirement: individual
	Hip cap start and end Requirement: individual			PVC solar through tile Length: ~ 45.7 cm Width: ~ 28.6 cm	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm ø: 30/50/70 mm
	Hip cap start and end with four outlets Requirement: individual			PVC solar carrier tile Length: ~ 45.7 cm Width: ~ 28.6 cm	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm Requirement: individual
	Clay dormer ventilator (ventilation cross-section ~ 15 cm²) Length: ~ 45.7 cm Width: ~ 28.6 cm Weight: ~ 3.7 kg	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm Requirement: individual		Light tile „Acrylic glass“ Length: ~ 45.7 cm Width: ~ 28.6 cm	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm Requirement: individual
	Ridge connection sliding tile Length: ~ 45.7 cm Width: ~ 28.6 cm	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm		2 Alu-walking grid tile, coated Length: ~ 40.0 cm Width: ~ 80.0 cm Weight: ~ 150.0 cm	
	Ridge connection sliding verge tile with outer web on left Length: ~ 45.7 cm Width: ~ 24.9 cm	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 22.0 cm		SnapStep universal alu step coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°	
	Ridge connection sliding verge tile with outer web on right Length: ~ 45.7 cm Width: ~ 24.1 cm	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 16.0 cm		SnapStep 40 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°	
	Shed roof tile Length: individual Width: ~ 28.6 cm	Covering length: individual Covering width: ~ 23.6 cm		SnapStep 80 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°	
	Shed roof-verge tile with outer web on left Length: individual Width: ~ 24.9 cm	Covering length: individual Covering width: ~ 22.0 cm		Alu base tile with single step Length: ~ 45.7 cm Width: ~ 28.6 cm	Covering length: ~ 34.5 cm ± 20 mm Covering width: ~ 23.6 cm Requirement: individual
	Shed roof-verge tile with outer web on right Length: individual Width: ~ 24.1 cm	Covering length: individual Covering width: ~ 16.0 cm			

* Over 42° RP = special design of PVC on request

Last revised 07/2010

Moulded tiles and accessories for the flat roof tile F 12 Ü

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.



Alu base pantile with twin tube holder

Length: ~ 45.7 cm Covering length: ~ 34.5 cm ± 20 mm
Width: ~ 28.6 cm Covering width: ~ 23.6 cm
Requirement: individual



Alu tile with round wood holder

Length: ~ 45.7 cm Covering length: ~ 34.5 cm ± 20 mm
Width: ~ 28.6 cm Covering width: ~ 23.6 cm
Requirement: individual



Alu tile with snow rib support

Length: ~ 45.7 cm Covering length: ~ 34.5 cm ± 20 mm
Width: ~ 28.6 cm Covering width: ~ 23.6 cm
Requirement: individual



Steel skylight, coated, 6-tiles, acrylic glazed

Length: ~ 78.0 cm Hatch: 45.0 x 55.0 cm
Width: ~ 76.0 cm Weight: ~ 8.6 kg



Steel skylight, coated, 9-tiles, acrylic glazed

Length: ~ 110.0 cm Hatch: 45.0 x 85.0 cm
Width: ~ 76.0 cm Weight: ~ 10.0 kg



Multitherm skylight

Length: ~ 85.0 cm Opening: upwards + to the side
Width: ~ 78.0 cm Hatch: 44.0 x 54.0 cm
Weight: ~ 15.0 kg Double glazing: ESG Kv 1.4



Living room skylight wra

Length: ~ 98.0 cm Opening: to the side
Width: ~ 54.0 cm Hatch: 46.0 x 90.0 cm
Double glazing: ESG Kv 1.1



Eaves fresh air element

~ 1.1 pcs/m



Ridge/crest lath holder



Ridge or crest clip no. 470/41



Copper roll/Alu roll 2000

Length: ~ 5 m Width: ~ 29 cm, 33 cm, 36 cm
Ventilation cross-section: permanent acc. to DIN 4108, Part 3
Natural copper, anthracite, red



Multi storm claw