




































Moulded tiles and accessories for the flat roof tile F 13 Classic

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.
















They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	Whole tile Length: ~ 43.8 cm Width: ~ 28.5 cm Weight: ~ 3.4 kg	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: ~ 12.2 pcs/m ²		Shed roof-Right verge tile Length: individual Width: ~ 28.3 cm	Covering length: individual Covering width: ~ 14.8 cm
	Double flap Length: ~ 43.8 cm Width: ~ 28.5 cm Weight: ~ 3.6 kg	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 28.5 cm Requirement: ~ 3.0 pcs/m		Mansard tile Length: individual Width: ~ 28.5 cm	Covering length: individual Covering width: ~ 22.4 cm
	Left verge tile Length: ~ 43.8 cm Width: ~ 28.7 cm Weight: ~ 5.1 kg	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 21.2 cm Requirement: ~ 3.0 pcs/m		Mansard-Double flap Length: individual Width: ~ 28.5 cm	Covering length: individual Covering width: ~ 28.5 cm
	Right verge tile Length: ~ 43.8 cm Width: ~ 28.3 cm Weight: ~ 5.0 kg	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 14.8 cm Requirement: ~ 3.0 pcs/m		Mansard-left verge tile Length: individual Width: ~ 28.7 cm	Covering length: individual Covering width: ~ 21.2 cm
	Ridge/crest tile ~ 2.7 pieces/m Length: ~ 43.5 cm Width: ~ 24.5 cm Weight: ~ 3.4 kg	Covering length: ~ 37.0 cm Covering width: ~ 21.2 cm Requirement: ~ 2.7 pcs/m		Mansard-right verge tile Length: individual Width: ~ 28.3 cm	Covering length: individual Covering width: ~ 14.8 cm
	Start ridge with offset end web for verge tile with offset ridge Length: ~ 43.5 cm Width: ~ 24.5 cm	Covering length: ~ 30.5 cm Covering width: ~ 21.2 cm		Pent roof tile Length: individual Width: ~ 28.5 cm	Covering length: individual Covering width: ~ 22.4 cm
	Ridge end with offset end web for verge tile with offset ridge Length: ~ 43.5 cm Width: ~ 24.5 cm	Covering length: ~ 37.0 cm Covering width: ~ 21.2 cm		Pent roof-Double flap Length: individual Width: ~ 28.5 cm	Covering length: individual Covering width: ~ 28.5 cm
	Crest initial tile Length: ~ 43.4 cm Width: ~ 23.1 cm Weight: ~ 3.2 kg	Covering length: ~ 29.5 cm Covering width: ~ 21.2 cm Requirement: individual		Pent roof-left verge tile Length: individual Width: ~ 28.7 cm	Covering length: individual Covering width: ~ 21.2 cm
	Hip cap start and end Requirement: individual			Pent roof-right verge tile Length: individual Width: ~ 28.3 cm	Covering length: individual Covering width: ~ 14.8 cm
	Hip cap start and end with four outlets Requirement: individual			Ceramic vent pipe tile with weather cap ø 125 and hose with adapter Length: ~ 43.8 cm Width: ~ 28.5 cm Weight: ~ 5.5 kg	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: individual
	Clay dormer ventilator (ventilation cross-section ~ 15 cm²) Length: ~ 43.8 cm Width: ~ 28.5 cm Weight: ~ 3.8 kg	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: individual		Ceramic aerial tile Length: ~ 43.8 cm Width: ~ 28.5 cm Weight: ~ 3.9 kg	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: individual
	Ridge connection sliding tile Length: ~ 43.8 cm Width: ~ 28.5 cm Max. displacement range 8.0 cm	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm		PVC thermal exhaust gas through tile ø 100/125 (can be used up a max of 45° RP*) Length: ~ 43.8 cm Width: ~ 28.5 cm	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm
	Ridge connection sliding Double flap Length: ~ 43.8 cm Width: ~ 28.5 cm Max. displacement range 8.0 cm	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 28.5 cm		Alu base tile with single step Length: ~ 43.8 cm Width: ~ 28.5 cm	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: individual
	Ridge connection sliding verge tile left Length: ~ 43.8 cm Width: ~ 28.7 cm Max. displacement range 8.0 cm	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 21.2 cm		Alu base pantile with twin tube holder Length: ~ 43.8 cm Width: ~ 28.5 cm	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: individual
	Ridge connection sliding verge tile right Length: ~ 43.8 cm Width: ~ 28.3 cm Max. displacement range 8.0 cm	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 14.8 cm		PVC solar through tile Length: ~ 43.8 cm Width: ~ 28.5 cm Weight: ~ 0.7 kg	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm ø: 30/50/70 mm
	Shed roof tile Length: individual Width: ~ 28.5 cm Weight: ~ 3.2 kg	Covering length: individual Covering width: ~ 22.4 cm		PVC solar carrier tile Length: ~ 43.8 cm Width: ~ 28.5 cm Weight: ~ 2.4 kg	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: individual
	Shed roof-Double flap Length: individual Width: ~ 28.5 cm	Covering length: individual Covering width: ~ 28.5 cm		Light tile „Acrylic glass“ Length: ~ 43.8 cm Width: ~ 28.5 cm	Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: individual
	Shed roof-left verge tile Length: individual Width: ~ 28.7 cm	Covering length: individual Covering width: ~ 21.2 cm			

Moulded tiles and accessories for the flat roof tile F 13 Classic

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	2 Alu-walking grid tile, coated Width: ~ 34.0 cm Length: 40.0; 80.0; 150.0 cm		Multitherm skylight Length: ~ 85.0 cm Width: ~ 78.0 cm Weight: ~ 15.0 kg Opening: upwards + to the side Hatch: 44.0 x 54.0 cm Double glazing: ESG Kv 1.4
	SnapStep universal alu step coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°		Living room skylight wra Length: ~ 98.0 cm Width: ~ 54.0 cm Opening: to the side Hatch: 46.0 x 90.0 cm Double glazing: ESG Kv 1.1
	SnapStep 40 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°		Eaves fresh air element ~ 1.1 pcs/m
	SnapStep 80 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°		Ridge/crest lath holder
	Alu tile with round wood holder Length: ~ 43.8 cm Width: ~ 28.5 cm Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: individual		Ridge or crest clip no. 470/41
	Alu tile with snow rib support Length: ~ 43.8 cm Width: ~ 28.5 cm Covering length: ~ 36.2 cm ± 5 mm Covering width: ~ 22.4 cm Requirement: individual		Copper roll/Alu roll 2000 Length: ~ 5 m Width: ~ 29 cm, 33 cm, 36 cm Ventilation cross-section: permanent acc. to DIN 4108, Part 3 Natural copper, anthracite, red
	Steel skylight, coated, 6-tiles, acrylic glazed Length: ~ 78.0 cm Width: ~ 76.0 cm Hatch: 45.0 x 55.0 cm Weight: ~ 8.6 kg		Storm clip no. 435/001 for laths 30 x 50 V2A (1) Storm clip no. 435/002 for laths 40 x 60 V2A (1) Storm clip no. 409/002 V2A (2)
	Steel skylight, coated, 9-tiles, acrylic glazed Length: ~ 110.0 cm Width: ~ 76.0 cm Hatch: 45.0 x 85.0 cm Weight: ~ 10.0 kg		