

Moulded tiles and accessories for the flat roof tile F 15

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	Whole tile Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.1 cm Covering width: ~ 19.9 cm Weight: ~ 3.1 kg Requirement: ~ 14.5 pcs/m ²		Shed roof-Double flap Length: individual Covering length: individual Width: ~ 28.5 cm Covering width: ~ 28.5 cm
	Three quarters tile Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 21.1 cm Covering width: ~ 15.0 cm Weight: ~ 2.7 kg Requirement: ~ 3.0 pcs/m		Shed roof-left verge tile Length: individual Covering length: individual Width: ~ 28.5 cm Covering width: ~ 19.0 cm
	Double flap Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 28.5 cm Covering width: ~ 28.5 cm Weight: ~ 3.3 kg Requirement: ~ 3.0 pcs/m		Shed roof-Right verge tile Length: individual Covering length: individual Width: ~ 26.7 cm Covering width: ~ 11.0 cm
	Left verge tile Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 28.5 cm Covering width: ~ 19.0 cm Weight: ~ 4.3 kg Requirement: ~ 3.0 pcs/m		Shed roof-verge tile with outer web on left Length: individual Covering length: individual Width: ~ 26.4 cm Covering width: ~ 22.0 cm
	Right verge tile Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.7 cm Covering width: ~ 11.0 cm Weight: ~ 4.0 kg Requirement: ~ 3.0 pcs/m		Shed roof-verge tile with outer web on right Length: individual Covering length: individual Width: ~ 26.1 cm Covering width: ~ 16.5 cm
	Verge tile with outer web on left (min. lath size 34.4 cm) Length: ~ 42.0 cm Covering length: ~ 34.4 - 35.2 cm Width: ~ 26.4 cm Covering width: ~ 22.0 cm		Eaves tile Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.1 cm Covering width: ~ 19.9 cm Weight: ~ 3.2 kg
	Verge tile with outer web on right (min. lath size 34.4 cm) Length: ~ 42.0 cm Covering length: ~ 34.4 - 35.2 cm Width: ~ 26.1 cm Covering width: ~ 16.5 cm		Three quarter eaves tile Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 21.1 cm Covering width: ~ 15.0 cm
	Clover leaf ridge tile ~ 2.7 pcs/m Length: ~ 42.5 cm Covering length: ~ 37.0 cm Width: ~ 28.0 cm Covering width: ~ 20.0 cm Weight: ~ 2.9 kg Requirement: ~ 2.7 pcs/m		Eaves Double flap Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 28.5 cm Covering width: ~ 28.5 cm
	Start ridge with offset end web for verge tile with offset ridge Length: ~ 42.0 cm Covering length: ~ 34.5 cm Weight: ~ 3.9 kg Requirement: individual		Eaves left verge tile Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 28.5 cm Covering width: ~ 19.0 cm
	Ridge end with offset end web for verge tile with offset ridge Length: ~ 42.0 cm Covering length: ~ 33.0 cm Weight: ~ 4.1 kg Requirement: individual		Eaves right verge tile Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.7 cm Covering width: ~ 11.0 cm
	Start ridge with extended web for verge tile with outer web Length: ~ 42.0 cm Covering length: ~ 34.5 cm Weight: ~ 3.9 kg Requirement: individual		Eaves-verge tile with outer web on left Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.4 cm Covering width: ~ 22.0 cm
	Ridge end with extended web for verge tile with outer web Length: ~ 42.0 cm Covering length: ~ 33.0 cm Weight: ~ 4.1 kg Requirement: individual		Eaves-verge tile with outer web on right Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.1 cm Covering width: ~ 16.5 cm
	Crest initial tile Length: ~ 42.0 cm Covering length: ~ 36.0 cm Weight: ~ 3.5 kg Requirement: individual		Ceramic aerial tile Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.1 cm Covering width: ~ 19.9 cm Weight: ~ 4.0 kg Requirement: individual
	Hip cap start and end Requirement: individual		Ceramic vent pipe tile with weather cap ø 125 and hose with adapter Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.1 cm Covering width: ~ 19.9 cm Requirement: individual
	Hip cap start and end with four outlets Requirement: individual		PVC thermal exhaust gas through tile ø 100/125 (can be used up a max of 40° RP*) Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.1 cm Covering width: ~ 19.9 cm
	Clay dormer ventilator (ventilation cross-section ~ 15 cm²) Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.1 cm Covering width: ~ 19.9 cm Weight: ~ 3.2 kg Requirement: individual		Light tile „Acrylic glass“ Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm Width: ~ 26.1 cm Covering width: ~ 19.9 cm Requirement: individual
	Shed roof tile Length: individual Covering length: individual Width: ~ 26.1 cm Covering width: ~ 19.9 cm		Walking grid tile PVC x 2 + walking grid Width: ~ 34.0 cm Length: 40.0; 80.0; 150.0 cm
	Three quarter shed roof tile Length: individual Covering length: individual Width: ~ 21.1 cm Covering width: ~ 15.0 cm		

Moulded tiles and accessories for the flat roof tile F 15

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.



SnapStep universal alu step
coated, for mounting on different lath thicknesses,
can be adjusted for roof
pitches from 0° - 60°



SnapStep 40 cm universal walking grid with two brackets
coated, for mounting on different lath thicknesses,
can be adjusted for roof
pitches from 0° - 60°



SnapStep 80 cm universal walking grid with two brackets
coated, for mounting on different lath thicknesses,
can be adjusted for roof
pitches from 0° - 60°



Safety step tile, PVC
Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm
Width: ~ 26.1 cm Covering width: ~ 19.9 cm
Weight: ~ 3.6 kg Requirement: individual



Snow stop tile with round wood holder PVC
Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm
Width: ~ 26.1 cm Covering width: ~ 19.9 cm



Snow stop tile with snow rib support PVC
Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm
Width: ~ 26.1 cm Covering width: ~ 19.9 cm



PVC solar carrier tile
Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm
Width: ~ 26.1 cm Covering width: ~ 19.9 cm
Requirement: individual



PVC solar through tile
Length: ~ 42.0 cm Covering length: ~ 34.7 cm ± 5 mm
Width: ~ 26.1 cm Covering width: ~ 19.9 cm
ø: 30/50/70 mm



Plastic skylight, 6-tiles, acrylic glazed
Length: ~ 75.0 cm Hatch: 47.5 x 52.0 cm
Width: ~ 65.0 cm Weight: ~ 5.0 kg



Steel skylight, coated, 6-tiles, acrylic glazed
Length: ~ 78.0 cm Hatch: 45.0 x 55.0 cm
Width: ~ 64.0 cm Weight: ~ 8.6 kg



Steel skylight, coated, 9-tiles, acrylic glazed
Length: ~ 110.0 cm Hatch: 45.0 x 85.0 cm
Width: ~ 64.0 cm Weight: ~ 11.0 kg




Multitherm skylight
Length: ~ 85.0 cm Opening: upwards + to the side
Width: ~ 78.0 cm Hatch: 44.0 x 54.0 cm
Weight: ~ 15.0 kg Double glazing: ESG Kv 1.4



Living room skylight wra
Length: ~ 98.0 cm Opening: to the side
Width: ~ 54.0 cm Hatch: 46.0 x 90.0 cm
Double glazing: ESG Kv 1.1



Eaves fresh air element
~ 1.1 pcs/m



Ridge/crest lath holder



Ridge or crest clip no. 470/121



Copper roll/Alu roll 2000
Length: ~ 5 m Width: ~ 29 cm, 33 cm, 36 cm
Ventilation cross-section: permanent acc. to DIN 4108, Part 3
Natural copper, anthracite, red



Storm clip no. 435/001 for laths 30 x 50 V2A (1)
Storm clip no. 435/002 for laths 40 x 60 V2A (1)
Storm clip no. 409/002 V2A (2)