

Moulded tiles and accessories for the NIBRA® flat tile G 10

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	Whole tile Length: ~ 48.2 cm Width: ~ 29.3 cm Weight: ~ 4.4 kg	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm Requirement: ~ 10.0 pcs/m ²		Shed roof tile Length: individual Width: ~ 29.3 cm	Covering length: individual Covering width: ~ 25.0 cm
	Large-area tile with nail hole* Length: ~ 48.2 cm Width: ~ 29.3 cm Weight: ~ 4.4 kg	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm Requirement: ~ 10.0 pcs/m ²		Shed roof-Double flap Length: individual Width: ~ 24.5 cm	Covering length: individual Covering width: ~ 24.5 cm
	Half tile Length: ~ 48.2 cm Width: ~ 16.8 cm Weight: ~ 2.5 kg	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 12.5 cm Requirement: individual		Shed roof-verge tile with outer web on left Length: individual Width: ~ 22.8 cm	Covering length: individual Covering width: ~ 21.0 cm
	Double flap Length: ~ 48.2 cm Width: ~ 24.5 cm Weight: ~ 3.7 kg	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 24.5 cm Requirement: ~ 2.5 pcs/m		Shed roof-verge tile with outer web on right Length: individual Width: ~ 22.8 cm	Covering length: individual Covering width: ~ 16.5 cm
	Verge tile with outer web on left Length: ~ 48.2 cm Width: ~ 22.8 cm Weight: ~ 5.1 kg	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 21.0 cm Requirement: ~ 2.5 pcs/m		Ceramic vent pipe tile with weather cap ø 150 and matching hose with adapter Length: ~ 48.2 cm Width: ~ 29.3 cm Weight: ~ 4.3 kg	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm
	Verge tile with outer web on right Length: ~ 48.2 cm Width: ~ 22.8 cm Weight: ~ 5.1 kg	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 16.5 cm Requirement: ~ 2.5 pcs/m		Ceramic aerial tile Length: ~ 48.2 cm Width: ~ 29.3 cm	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm
	Clay dormer ventilator (ventilation cross-section ~ 20 cm²) Length: ~ 48.2 cm Width: ~ 29.3 cm Weight: ~ 4.3 kg	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm Requirement: individual		Ceramic thermal exhaust gas through pantile with universal collar (ø: max. 127 mm) (can be used up a max of 42° RP) Length: ~ 48.2 cm Width: ~ 29.3 cm	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm
	Standard ridge tile ~ 2.6 pcs/m Length: ~ 43.7 cm Width: ~ 25.4 cm Weight: ~ 3.6 kg	Covering length: ~ 38.2 cm Covering width: ~ 19.6 cm Requirement: ~ 2.6 pcs/m		PVC solar carrier tile Length: ~ 48.2 cm Width: ~ 29.3 cm	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm Requirement: individual
	Standard start ridge with extended web for verge tile with outer web Length: ~ 43.7 cm Width: ~ 25.4 cm	Covering length: ~ 38.2 cm Covering width: ~ 19.6 cm		Ceramic solar through tile up to ø 70 mm Length: ~ 48.2 cm Width: ~ 29.3 cm ø: ≤ 70 mm	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm
	Standard ridge end with extended web for verge tile with outer web Length: ~ 38.0 cm Width: ~ 25.4 cm	Covering length: ~ 36.0 cm Covering width: ~ 19.6 cm		Light tile „Acrylic glass“ Length: ~ 48.2 cm Width: ~ 29.3 cm	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm Requirement: individual
	Universal hip cap Weight: ~ 4.5 kg	Requirement: individual		2 Alu-walking grid tile, coated Width: ~ 34.0 cm Length: 40.0; 80.0; 150.0 cm	
	Universal hip cap with four outlets Weight: ~ 6.3 kg	Requirement: individual		SnapStep universal alu step coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°	
	Standard crest start Length: ~ 49.0 cm Width: ~ 22.2 cm Weight: ~ 3.5 kg	Covering length: ~ 43.9 cm Covering width: ~ 19.8 cm Requirement: individual		SnapStep 40 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°	
	Square ridge tile ~ 2.5 pcs/m Length: ~ 43.6 cm Width: ~ 25.6 cm Weight: ~ 4.3 kg	Covering length: ~ 38.0 cm Covering width: ~ 17.3 cm Requirement: ~ 2.5 pcs/m		SnapStep 80 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°	
	Square start ridge with extended web for verge tile with outer web Length: ~ 43.6 cm Width: ~ 25.6 cm	Covering length: ~ 38.7 cm Covering width: ~ 17.3 cm		Alu base tile with single step Length: ~ 48.2 cm Width: ~ 29.3 cm	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm Requirement: individual
	Square ridge end with extended web for verge tile with outer web Length: ~ 38.0 cm Width: ~ 25.6 cm	Covering length: ~ 35.6 cm Covering width: ~ 17.3 cm		Alu base pantile with twin tube holder Length: ~ 48.2 cm Width: ~ 29.3 cm	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm Requirement: individual
	Square hip cap start and end Weight: ~ 4.5 kg	Requirement: individual		Alu tile with round wood holder Length: ~ 48.2 cm Width: ~ 29.3 cm	Covering length: ~ 39.1 cm ± 10 mm Covering width: ~ 25.0 cm Requirement: individual
	Universal square hip cap with four outlets Weight: ~ 5.7 kg	Requirement: individual			

* Delivery period on request

* Over 42° RP = special design of PVC on request

Moulded tiles and accessories for the NIBRA® flat tile G 10

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs. They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.



Alu tile with snow rib support

Length: ~ 48.2 cm Covering length: ~ 39.1 cm ± 10 mm
 Width: ~ 29.3 cm Covering width: ~ 25.0 cm
 Requirement: individual



Steel skylight, coated, 5-tiles, acrylic glazed

(4 whole + 2 half tiles)
 Hatch: 45.0 x 55.0 cm



Multitherm skylight

Length: ~ 85.0 cm Opening: upwards + to the side
 Width: ~ 78.0 cm Hatch: 44.0 x 54.0 cm
 Weight: ~ 15.0 kg Double glazing: ESG Kv 1.4



Living room skylight wra

Length: ~ 98.0 cm Opening: to the side
 Width: ~ 54.0 cm Hatch: 46.0 x 90.0 cm
 Double glazing: ESG Kv 1.1



Eaves fresh air element

~ 1.1 pcs/m



Ridge/crest lath holder



Ridge or crest clip no. 470/41 (standard ridge)



Ridge or crest clip no. 470/166 (square ridge)



Copper roll/Alu roll 2000

Length: ~ 5 m Width: ~ 29 cm, 33 cm, 36 cm
 Ventilation cross-section: permanent acc. to DIN 4108, Part 3
 Natural copper, anthracite, red



Storm clip no. 409/008 V2A