

# Moulded tiles and accessories for the NIBRA<sup>®</sup> hollow interlocking tile H 10

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	<b>Whole tile</b> Length: ~ 48.4 cm Width: ~ 29.7 cm Weight: ~ 4.6 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 24.6 cm Requirement: ~ 10.3 pcs/m <sup>2</sup>		<b>Ridge connecting Double flap</b> Length: ~ 48.4 cm Width: ~ 32.1 cm	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 32.1 cm
	<b>Large-area tile with nail hole*</b> Length: ~ 48.4 cm Width: ~ 29.7 cm Weight: ~ 4.6 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 24.6 cm Requirement: ~ 10.3 pcs/m <sup>2</sup>		<b>Ridge connection-verge tile left</b> Length: ~ 48.4 cm Width: ~ 32.1 cm	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 19.5 cm
	<b>Single rabbet tile*</b> Length: ~ 48.4 cm Width: ~ 29.7 cm Weight: ~ 4.3 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 24.6 cm Requirement: individual		<b>Ridge connection-verge tile right</b> Length: ~ 48.4 cm Width: ~ 29.7 cm	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 12.0 cm
	<b>Double flap</b> Length: ~ 48.4 cm Width: ~ 32.1 cm Weight: ~ 4.1 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 32.1 cm Requirement: ~ 2.5 pcs/m		<b>Ridge connection-verge tile with outer web on left (Not available in all colours)</b> Length: ~ 48.4 cm Width: ~ 29.9 cm	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 27.8 cm
	<b>Left verge tile</b> Length: ~ 48.4 cm Width: ~ 32.1 cm Weight: ~ 5.5 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 19.5 cm Requirement: ~ 2.5 pcs/m		<b>Ridge connection-verge tile with outer web on right (Not available in all colours)</b> Length: ~ 48.4 cm Width: ~ 26.8 cm	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 20.1 cm
	<b>Right verge tile</b> Length: ~ 48.4 cm Width: ~ 29.7 cm Weight: ~ 5.3 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 12.0 cm Requirement: ~ 2.5 pcs/m		<b>Ridge tile extra ~ 2.6 pcs/m (matches ridge connecting tile)</b> Length: ~ 44.0 cm Width: ~ 27.0 cm	Covering length: ~ 38.5 cm Covering width: ~ 21.2 cm
	<b>Verge tile with outer web on left (Not available in all colours)</b> Length: ~ 48.4 cm Width: ~ 29.9 cm Weight: ~ 6.7 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 27.8 cm Requirement: ~ 2.5 pcs/m		<b>Start ridge extra closed at bottom for verge tile with offset web</b> Length: ~ 44.0 cm Width: ~ 27.0 cm	Covering length: ~ 38.5 cm Covering width: ~ 21.2 cm
	<b>Verge tile with outer web on right (Not available in all colours)</b> Length: ~ 48.4 cm Width: ~ 26.8 cm Weight: ~ 5.8 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 20.1 cm Requirement: ~ 2.5 pcs/m		<b>End ridge extra closed at bottom for verge tile with offset web</b> Length: ~ 38.3 cm Width: ~ 27.0 cm	Covering length: ~ 36.3 cm Covering width: ~ 21.2 cm
	<b>Standard ridge tile ~ 2.6 pcs/m</b> Length: ~ 43.7 cm Width: ~ 25.4 cm Weight: ~ 3.6 kg	Covering length: ~ 38.2 cm Covering width: ~ 19.6 cm Requirement: ~ 2.6 pcs/m		<b>Start ridge extra with extended web for verge tile with outer web</b> Length: ~ 44.0 cm Width: ~ 27.0 cm	Covering length: ~ 38.5 cm Covering width: ~ 21.2 cm
	<b>Standard start ridge, bottom closed for verge tile with offset ridge</b> Length: ~ 43.7 cm Width: ~ 25.4 cm	Covering length: ~ 38.2 cm Covering width: ~ 19.6 cm		<b>End ridge extra with extended web for verge tile with outer web</b> Length: ~ 38.3 cm Width: ~ 27.0 cm	Covering length: ~ 36.3 cm Covering width: ~ 21.2 cm
	<b>Standard ridge end, bottom closed for verge tile with offset ridge</b> Length: ~ 38.0 cm Width: ~ 25.4 cm	Covering length: ~ 36.0 cm Covering width: ~ 19.6 cm		<b>Shed roof tile</b> Length: individual Width: ~ 29.7 cm	Covering length: individual Covering width: ~ 24.6 cm
	<b>Standard start ridge with extended web for verge tile with outer web</b> Length: ~ 43.7 cm Width: ~ 25.4 cm	Covering length: ~ 38.2 cm Covering width: ~ 19.6 cm		<b>Shed roof-Double flap</b> Length: individual Width: ~ 32.1 cm	Covering length: individual Covering width: ~ 32.1 cm
	<b>Standard ridge end with extended web for verge tile with outer web</b> Length: ~ 38.0 cm Width: ~ 25.4 cm	Covering length: ~ 36.0 cm Covering width: ~ 19.6 cm		<b>Shed roof-left verge tile</b> Length: individual Width: ~ 32.1 cm	Covering length: individual Covering width: ~ 19.5 cm
	<b>Standard crest start</b> Length: ~ 49.0 cm Width: ~ 25.4 cm Weight: ~ 3.5 kg	Covering length: ~ 43.9 cm Covering width: ~ 19.6 cm Requirement: individual		<b>Shed roof-Right verge tile</b> Length: individual Width: ~ 29.7 cm	Covering length: individual Covering width: ~ 12.0 cm
	<b>Universal hip cap</b> Weight: ~ 4.5 kg	Requirement: individual		<b>Shed roof-verge tile with outer web on left (Not available in all colours)</b> Length: individual Width: ~ 29.9 cm	Covering length: individual Covering width: ~ 27.8 cm
	<b>Universal hip cap with four outlets</b> Weight: ~ 6.3 kg	Requirement: individual		<b>Shed roof-verge tile with outer web on right (Not available in all colours)</b> Length: individual Width: ~ 26.8 cm	Covering length: individual Covering width: ~ 20.1 cm
	<b>Clay dormer ventilator (ventilation cross-section ~ 17 cm<sup>2</sup>)</b> Length: ~ 48.4 cm Width: ~ 29.7 cm Weight: ~ 4.5 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 24.6 cm Requirement: individual		<b>Eaves tile</b> Length: ~ 48.4 cm Width: ~ 29.7 cm Weight: ~ 4.6 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 24.6 cm Requirement: ~ 4.0 pcs/m
	<b>Ridge connecting tile</b> Length: ~ 48.4 cm Width: ~ 29.7 cm Weight: ~ 4.1 kg	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 24.6 cm		<b>Eaves Double flap</b> Length: ~ 48.4 cm Width: ~ 32.1 cm	Covering length: ~ 38.3 cm ± 15 mm Covering width: ~ 32.1 cm

# Moulded tiles and accessories for the NIBRA® hollow interlocking tile H 10

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.


	<b>Eaves left verge tile</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 32.1 cm    Covering width: ~ 19.5 cm		<b>Ceramic aerial tile</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 24.6 cm Weight: ~ 5.0 kg
	<b>Eaves right verge tile</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 12.0 cm		<b>Ceramic thermal exhaust gas through pantile with universal collar (ø: max. 127 mm) (can be used up a max of 42° RP*)</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 24.6 cm
	<b>Eaves-verge tile with outer web on left</b> <b>(Not available in all colours)</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.9 cm    Covering width: ~ 27.8 cm		<b>PVC solar carrier tile</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 24.6 cm
	<b>Eaves-verge tile with outer web on right</b> <b>(Not available in all colours)</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 26.8 cm    Covering width: ~ 20.1 cm		<b>Ceramic solar through tile up to ø 70 mm</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 24.6 cm ø: ≤ 70 mm
	<b>Mansard tile</b> Length: individual    Covering length: individual Width: ~ 29.7 cm    Covering width: ~ 24.6 cm		<b>Light tile „Acrylic glass“</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 24.6 cm
	<b>Mansard-Double flap</b> Length: individual    Covering length: individual Width: ~ 32.1 cm    Covering width: ~ 32.1 cm		<b>Walking grid tile PVC x 2 + walking grid</b> Width: ~ 34.0 cm Length: 40.0; 80.0; 150.0 cm
	<b>Mansard-left verge tile</b> Length: individual    Covering length: individual Width: ~ 32.1 cm    Covering width: ~ 19.5 cm		<b>SnapStep 40 cm universal walking grid with two brackets</b> coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°
	<b>Mansard-right verge tile</b> Length: individual    Covering length: individual Width: ~ 29.7 cm    Covering width: ~ 12.0 cm		<b>SnapStep 80 cm universal walking grid with two brackets</b> coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°
	<b>Mansard-verge tile with outer web on left</b> <b>(Not available in all colours)</b> Length: individual    Covering length: individual Width: ~ 29.9 cm    Covering width: ~ 27.8 cm		<b>Safety step tile, PVC</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 24.6 cm Weight: ~ 3.8 kg
	<b>Mansard-verge tile with outer web on right</b> <b>(Not available in all colours)</b> Length: individual    Covering length: individual Width: ~ 26.8 cm    Covering width: ~ 20.1 cm		<b>Snow stop tile with round wood holder PVC</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 24.6 cm
	<b>Pent roof tile</b> Length: individual    Covering length: individual Width: ~ 29.7 cm    Covering width: ~ 24.6 cm		<b>Snow stop tile with snow rib support PVC</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 24.6 cm
	<b>Pent roof-Double flap</b> Length: individual    Covering length: individual Width: ~ 32.1 cm    Covering width: ~ 32.1 cm		<b>Steel skylight, coated, 4-tiles, acrylic glazed</b> Length: ~ 91.0 cm    Hatch: 45.0 x 55.0 cm Width: ~ 83.0 cm    Weight: ~ 10.0 kg
	<b>Pent roof-left verge tile</b> Length: individual    Covering length: individual Width: ~ 32.1 cm    Covering width: ~ 19.5 cm		<b>Multitherm skylight</b> Length: ~ 85.0 cm    Opening: upwards + to the side Width: ~ 78.0 cm    Hatch: 44.0 x 54.0 cm Weight: ~ 15.0 kg    Double glazing: ESG Kv 1.4
	<b>Pent roof-right verge tile</b> Length: individual    Covering length: individual Width: ~ 29.7 cm    Covering width: ~ 12.0 cm		<b>Living room skylight wra</b> Length: ~ 98.0 cm    Opening: to the side Width: ~ 54.0 cm    Hatch: 46.0 x 90.0 cm Double glazing: ESG Kv 1.1
	<b>Pent roof-verge tile with outer web on left</b> <b>(Not available in all colours)</b> Length: individual    Covering length: individual Width: ~ 29.9 cm    Covering width: ~ 27.8 cm		<b>Eaves fresh air element</b> ~ 1.1 pcs/m
	<b>Pent roof-verge tile with outer web on right</b> <b>(Not available in all colours)</b> Length: individual    Covering length: individual Width: ~ 26.8 cm    Covering width: ~ 20.1 cm		<b>Ridge/crest lath holder</b>
	<b>Ceramic vent pipe tile with weather cap ø 150 and matching hose with adapter</b> Length: ~ 48.4 cm    Covering length: ~ 38.3 cm ± 15 mm Width: ~ 29.7 cm    Covering width: ~ 24.6 cm Weight: ~ 4.8 kg		<b>Ridge or crest clip no. 470/41</b>
			<b>Copper roll/Alu roll 2000</b> Length: ~ 5 m    Width: ~ 29 cm, 33 cm, 36 cm Ventilation cross-section: permanent acc. to DIN 4108, Part 3 Natural copper, anthracite, red

\* Over 42° RP = special design of PVC on request

Last revised 05/2010

# Moulded tiles and accessories for the NIBRA<sup>®</sup> hollow interlocking tile H 10

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs. They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.



Storm clip no. 435/101 for laths 30 x 50 V2A (1)

Storm clip no. 435/102 for laths 40 x 60 V2A (1)

Storm clip no. 409/009 V2A (2)