
























Moulded tiles and accessories for the hollow tile

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	Whole tile Length: ~ 39.3 cm Width: ~ 24.5 cm Weight: ~ 2.5 kg	Covering length: max. ~ 32.3 cm Covering width: ~ 19.5 cm Requirement: ~ 16.0 pcs/m ²		Ceramic vent pipe tile with weather cap ø 125 and hose with adapter Length: ~ 39.3 cm Width: ~ 24.5 cm	Covering length: max. ~ 32.3 cm Covering width: ~ 19.5 cm Requirement: individual
	Double flap Length: ~ 39.3 cm Width: ~ 28.0 cm Weight: ~ 3.5 kg	Covering length: max. ~ 32.3 cm Covering width: ~ 28.0 cm		SnapStep universal alu step coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°	
	Left verge tile Length: ~ 39.3 cm Width: ~ 28.8 cm	Covering length: max. ~ 32.3 cm Covering width: ~ 25.0 cm		SnapStep 40 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°	
	Right verge tile Length: ~ 39.3 cm Width: ~ 24.9 cm	Covering length: max. ~ 32.3 cm Covering width: ~ 16.0 cm		SnapStep 80 cm universal walking grid with two brackets coated, for mounting on different lath thicknesses, can be adjusted for roof pitches from 0° - 60°	
	Universal ridge/crest tile ~ 3.0 pieces/m Length: ~ 41.8 cm Width: ~ 23.7 cm	Covering length: ~ 33.0 cm Covering width: ~ 21.0 cm Requirement: ~ 3.0 pcs/m		Ceramic aerial tile Length: ~ 39.3 cm Width: ~ 24.5 cm	Covering length: max. ~ 32.3 cm Covering width: ~ 19.5 cm Requirement: individual
	Universal start ridge with extended end web for verge tile with outer web Length: ~ 43.9 cm Width: ~ 23.7 cm	Covering length: ~ 40.0 cm Covering width: ~ 21.0 cm		PVC thermal exhaust gas through tile ø 100/125 (can be used up a max of 35° RP*) Length: ~ 39.3 cm Width: ~ 24.5 cm	Covering length: max. ~ 32.3 cm Covering width: ~ 19.5 cm
	Universal end ridge with extended end web for verge tile with outer web Length: ~ 43.8 cm Width: ~ 23.9 cm	Covering length: ~ 40.5 cm Covering width: ~ 21.2 cm		Light tile „Acrylic glass“ Length: ~ 39.3 cm Width: ~ 24.5 cm	Covering length: max. ~ 32.3 cm Covering width: ~ 19.5 cm Requirement: individual
	Universal crest initial tile Length: ~ 43.4 cm Width: ~ 23.7 cm Weight: ~ 3.2 kg	Covering length: ~ 29.5 cm Covering width: ~ 21.0 cm Requirement: individual		Eaves fresh air element ~ 1.1 pcs/m	
	Universal hip cap for start and end Requirement: individual			Ridge/crest lath holder	
	Universal hip cap for start and end with four outlets Requirement: individual			Ridge or crest clip no. 470/41	
	Clay dormer ventilator (ventilation cross-section ~ 15 cm²) Length: ~ 39.3 cm Width: ~ 24.5 cm	Covering length: max. ~ 32.3 cm Covering width: ~ 19.5 cm Requirement: individual		Copper roll/Alu roll 2000 Length: ~ 5 m Width: ~ 29 cm, 33 cm, 36 cm	Ventilation cross-section: permanent acc. to DIN 4108, Part 3 Natural copper, anthracite, red
				Storm clip no. 428b01 for laths 30 x 50 Storm clip no. 428b02 for laths 40 x 60	

* Over 35° RP = special design on request