



































# Moulded tiles and accessories for the NIBRA<sup>®</sup> flat tile S 9

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.

	<b>Whole tile</b> Length: ~ 49.4 cm Width: ~ 29.2 cm Weight: ~ 4.3 kg	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: ~ 9.2 pcs/m <sup>2</sup>		<b>Universal square hip cap with four outlets</b> Weight: ~ 5.7 kg	Requirement: individual
	<b>Large-area tile with nail hole*</b> Length: ~ 49.4 cm Width: ~ 29.2 cm Weight: ~ 4.3 kg	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: individual		<b>Shed roof tile</b> Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 26.8 cm
	<b>Half tile</b> Length: ~ 49.4 cm Width: ~ 16.0 cm Weight: ~ 2.1 kg	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 13.4 cm Requirement: individual		<b>Shed roof-Double flap</b> Length: individual Width: ~ 29.2 cm	Covering length: individual Covering width: ~ 29.2 cm
	<b>Half tile with nail hole</b> Length: ~ 49.4 cm Width: ~ 16.0 cm Weight: ~ 2.1 kg	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 13.4 cm Requirement: individual		<b>Shed roof-verge tile with outer web on left</b> Length: individual Width: ~ 13.5 cm	Covering length: individual Covering width: ~ 11.7 cm
	<b>Double flap</b> Length: ~ 49.4 cm Width: ~ 29.2 cm Weight: ~ 4.1 kg	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 29.2 cm Requirement: ~ 2.6 pcs/m		<b>Shed roof-verge tile with outer web on right</b> Length: individual Width: ~ 16.4 cm	Covering length: individual Covering width: ~ 12.1 cm
	<b>Sliding verge tile with outer web on left</b> Length: ~ 49.4 cm Width: ~ 13.5 cm Weight: ~ 2.9 kg	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 11.7 cm Requirement: ~ 2.6 pcs/m		<b>Ceramic aerial tile</b> Length: ~ 49.4 cm Width: ~ 29.2 cm	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: individual
	<b>Sliding verge tile with outer web on right</b> Length: ~ 49.4 cm Width: ~ 16.4 cm Weight: ~ 3.2 kg	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 12.1 cm Requirement: ~ 2.6 pcs/m		<b>Ceramic vent pipe tile with weather cap ø 150 and matching hose with adapter</b> Length: ~ 49.4 cm Width: ~ 29.2 cm	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: individual
	<b>Clay dormer ventilator (ventilation cross-section ~ 20 cm<sup>2</sup>)</b> Length: ~ 49.4 cm Width: ~ 29.2 cm Weight: ~ 3.8 kg	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: individual		<b>Ceramic thermal exhaust gas through pantile with universal collar (ø: max. 127 mm) (can be used up a max of 42° RP*)</b> Length: ~ 49.4 cm Width: ~ 29.2 cm	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm
	<b>Standard ridge tile ~ 2.6 pcs/m</b> Length: ~ 43.7 cm Width: ~ 25.4 cm Weight: ~ 3.6 kg	Covering length: ~ 38.2 cm Covering width: ~ 19.6 cm Requirement: ~ 2.6 pcs/m		<b>Ceramic solar through tile up to ø 70 mm</b> Length: ~ 49.4 cm Width: ~ 29.2 cm	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm ø: ≤ 70 mm
	<b>Standard start ridge with extended web for verge tile with outer web</b> Length: ~ 43.7 cm Width: ~ 25.4 cm	Covering length: ~ 38.2 cm Covering width: ~ 19.6 cm		<b>PVC solar carrier tile</b> Length: ~ 49.4 cm Width: ~ 29.2 cm	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: individual
	<b>Standard ridge end with extended web for verge tile with outer web</b> Length: ~ 38.0 cm Width: ~ 25.4 cm	Covering length: ~ 36.0 cm Covering width: ~ 19.6 cm		<b>Light tile „Acrylic glass“</b> Length: ~ 49.4 cm Width: ~ 29.2 cm	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: individual
	<b>Standard crest start</b> Length: ~ 49.0 cm Width: ~ 25.4 cm Weight: ~ 3.5 kg	Covering length: ~ 43.9 cm Covering width: ~ 19.6 cm Requirement: individual		<b>Walking grid tile PVC x 2 + walking grid</b> Width: ~ 34.0 cm Length: 40.0; 80.0; 150.0 cm	
	<b>Universal hip cap</b> Weight: ~ 4.5 kg	Requirement: individual		<b>Safety step tile, PVC</b> Length: ~ 49.4 cm Width: ~ 29.2 cm	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: individual
	<b>Universal hip cap with four outlets</b> Weight: ~ 6.3 kg	Requirement: individual		<b>Snow stop tile with round wood holder PVC</b> Length: ~ 49.4 cm Width: ~ 29.2 cm	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: individual
	<b>Square ridge tile ~ 2.5 pcs/m</b> Length: ~ 43.6 cm Width: ~ 25.6 cm Weight: ~ 4.3 kg	Covering length: ~ 38.0 cm Covering width: ~ 17.3 cm Requirement: ~ 2.5 pcs/m		<b>Snow stop tile with snow rib support PVC</b> Length: ~ 49.4 cm Width: ~ 29.2 cm	Covering length: ~ 33.0 - 40.0 cm Covering width: ~ 26.8 cm Requirement: individual
	<b>Square start ridge end with extended web for verge tile with outer web</b> Length: ~ 43.6 cm Width: ~ 25.6 cm	Covering length: ~ 38.7 cm Covering width: ~ 17.3 cm		<b>Steel skylight, coated, 4-tiles, acrylic glazed</b> Length: ~ 91.0 cm Width: ~ 83.0 cm	Hatch: 42.0 x 52.0 cm Weight: ~ 10.0 kg
	<b>Square ridge end end with extended web for verge tile with outer web</b> Length: ~ 38.0 cm Width: ~ 25.6 cm	Covering length: ~ 35.6 cm Covering width: ~ 17.3 cm		<b>Multitherm skylight</b> Length: ~ 85.0 cm Width: ~ 78.0 cm Weight: ~ 15.0 kg	Opening: upwards + to the side Hatch: 44.0 x 54.0 cm Double glazing: ESG Kv 1.4


\* Delivery period on request

\* Over 42° RP = special design of PVC on request

# Moulded tiles and accessories for the NIBRA® flat tile S 9

Moulded tiles for various functions meet the demand for homogeneous, architecturally demanding roofs.

They are also an important safety factor. Moulded tiles and accessories reduce the amount of laying work and facilitate calculations.



### Living room skylight wra

Length: ~ 98.0 cm    Opening: to the side  
 Width: ~ 54.0 cm    Hatch: 46.0 x 90.0 cm  
 Double glazing: ESG Kv 1.1



### Ridge or crest clip no. 470/166 (square ridge)

### Eaves fresh air element

~ 1.1 pcs/m



### Copper roll/Alu roll 2000

Length: ~ 5 m    Width: ~ 29 cm, 33 cm, 36 cm  
 Ventilation cross-section: permanent acc. to DIN 4108, Part 3  
 Natural copper, anthracite, red

### Ridge/crest lath holder



Storm clip no. 435/105 for laths 30 x 50 V2A  
 Storm clip no. 435/106 for laths 40 x 60 V2A

### Ridge or crest clip no. 470/41 (standard ridge)

